

manufacturer: ait-deutschland GmbH			
Model	cBoxX 30		
Option high-temperature	No		
Voltage <sup>1</sup>	400/3/60		
Type of condensing	air-cooled		
Refrigerant fluid	R410A		
Item	Symbol	Value	Unit
Operating temperature	t	7	°C
Seasonal energy performance ratio	SEPR	5,54	
Annual electricity consumption	Q	31.918	kWh/a
Parameters at full load and reference ambient temperature at rating point A			
Rated refrigeration capacity	P <sub>A</sub>	23,86	kW
Rated power input	D <sub>A</sub>	8,56	kW
Rated energy efficiency ratio	EER <sub>DC,A</sub>	2,79	
Parameters at rating point B			
Declared refrigeration capacity	P <sub>B</sub>	26,86	kW
Declared power input	D <sub>B</sub>	7,20	kW
Declared energy efficiency ratio	EER <sub>DC,B</sub>	3,73	
Parameters at rating point C			
Declared refrigeration capacity	P <sub>C</sub>	30,66	kW
Declared power input	D <sub>C</sub>	5,88	kW
Declared energy efficiency ratio	EER <sub>DC,C</sub>	5,21	
Parameters at rating point D			
Declared refrigeration capacity	P <sub>D</sub>	33,17	kW
Declared power input	D <sub>D</sub>	4,52	kW
Declared energy efficiency ratio	EER <sub>DC,D</sub>	7,34	
Other Items			
Capacity control	fixed		
Degradation co-efficient chillers (rating point B)	C <sub>dc</sub>	0,98	
Degradation co-efficient chillers (rating point C)	C <sub>dc</sub>	0,97	
Degradation co-efficient chillers (rating point D)	C <sub>dc</sub>	0,96	
GWP of the refrigerant		2088	kg CO <sub>2</sub> eq (100 years)

<sup>1</sup> The voltage refers to the operating voltage of the main components and can deviate from the supply voltage by using a transformer.