

manufacturer: ait-deutschland GmbH			
Model	cBoxX 30		
Option high-temperature	No		
Voltage ¹	460/3/60		
Type of condensing	water-cooled		
Refrigerant fluid	R410A		
Item	Symbol	Value	Unit
Operating temperature	t	7	°C
Seasonal energy performance ratio	SEPR	7,22	
Annual electricity consumption	Q	26.828	kWh/a
Parameters at full load and reference ambient temperature at rating point A			
Rated refrigeration capacity	P _A	26,14	kW
Rated power input	D _A	6,90	kW
Rated energy efficiency ratio	EER _{DC,A}	3,79	
Parameters at rating point B			
Declared refrigeration capacity	P _B	28,93	kW
Declared power input	D _B	5,64	kW
Declared energy efficiency ratio	EER _{DC,B}	5,13	
Parameters at rating point C			
Declared refrigeration capacity	P _C	30,89	kW
Declared power input	D _C	4,65	kW
Declared energy efficiency ratio	EER _{DC,C}	6,64	
Parameters at rating point D			
Declared refrigeration capacity	P _D	32,90	kW
Declared power input	D _D	3,42	kW
Declared energy efficiency ratio	EER _{DC,D}	9,62	
Other Items			
Capacity control	fixed		
Degradation co-efficient chillers (rating point B)	C _{dc}	0,96	
Degradation co-efficient chillers (rating point C)	C _{dc}	0,96	
Degradation co-efficient chillers (rating point D)	C _{dc}	0,94	
GWP of the refrigerant		2088	kg CO ₂ eq (100 years)

¹ The voltage refers to the operating voltage of the main components and can deviate from the supply voltage by using a transformer.