

manufacturer: ait-deutschland GmbH			
Model	cBoxX 40		
Option high-temperature	Yes		
Voltage <sup>1</sup>	400/3/50		
Type of condensing	air-cooled		
Refrigerant fluid	R410A		
Item	Symbol	Value	Unit
Operating temperature	t	-8	°C
Seasonal energy performance ratio	JAZ	3,32	
Annual electricity consumption	Q	38.363	kWh/a
Parameters at full load and reference ambient temperature at rating point A			
Rated refrigeration capacity	P <sub>A</sub>	17,17	kW
Rated power input	D <sub>A</sub>	9,98	kW
Rated energy efficiency ratio	LZ <sub>A</sub>	1,72	
Parameters at rating point B			
Declared refrigeration capacity	P <sub>B</sub>	19,63	kW
Declared power input	D <sub>B</sub>	8,24	kW
Declared energy efficiency ratio	LZ <sub>B</sub>	2,38	
Parameters at rating point C			
Declared refrigeration capacity	P <sub>C</sub>	21,92	kW
Declared power input	D <sub>C</sub>	6,91	kW
Declared energy efficiency ratio	LZ <sub>C</sub>	3,17	
Parameters at rating point D			
Declared refrigeration capacity	P <sub>D</sub>	24,11	kW
Declared power input	D <sub>D</sub>	5,71	kW
Declared energy efficiency ratio	LZ <sub>D</sub>	4,22	
Other Items			
Capacity control	fixed		
Degradation coefficient for fixed and staged capacity units (rating point B)	MK	0,97	
Degradation coefficient for fixed and staged capacity units (rating point C)	MK	0,97	
Degradation coefficient for fixed and staged capacity units (rating point D)	MK	0,96	
GWP of the refrigerant		2088	kg CO <sub>2</sub> eq (100 years)

<sup>1</sup> The voltage refers to the operating voltage of the main components and can deviate from the supply voltage by using a transformer.

