

| | | | |
|--|-----------------|--------|--------------------------------------|
| manufacturer: ait-deutschland GmbH | | | |
| Model | cBoxX 50 | | |
| Option high-temperature | No | | |
| Voltage ¹ | 400/3/50 | | |
| Type of condensing | water-cooled | | |
| Refrigerant fluid | R410A | | |
| | | | |
| Item | Symbol | Value | Unit |
| Operating temperature | t | -8 | °C |
| Seasonal energy performance ratio | JAZ | 3,86 | |
| Annual electricity consumption | Q | 45.885 | kWh/a |
| | | | |
| Parameters at full load and reference ambient temperature at rating point A | | | |
| Rated refrigeration capacity | P _A | 23,89 | kW |
| Rated power input | D _A | 10,70 | kW |
| Rated energy efficiency ratio | LZ _A | 2,23 | |
| | | | |
| Parameters at rating point B | | | |
| Declared refrigeration capacity | P _B | 26,71 | kW |
| Declared power input | D _B | 8,98 | kW |
| Declared energy efficiency ratio | LZ _B | 2,97 | |
| | | | |
| Parameters at rating point C | | | |
| Declared refrigeration capacity | P _C | 28,74 | kW |
| Declared power input | D _C | 7,83 | kW |
| Declared energy efficiency ratio | LZ _C | 3,67 | |
| | | | |
| Parameters at rating point D | | | |
| Declared refrigeration capacity | P _D | 30,93 | kW |
| Declared power input | D _D | 6,56 | kW |
| Declared energy efficiency ratio | LZ _D | 4,71 | |
| | | | |
| Other Items | | | |
| Capacity control | staged | | |
| Degradation coefficient for fixed and staged capacity units (rating point B) | MK | 0,97 | |
| Degradation coefficient for fixed and staged capacity units (rating point C) | MK | 0,97 | |
| Degradation coefficient for fixed and staged capacity units (rating point D) | MK | 0,96 | |
| GWP of the refrigerant | | 2089 | kg CO ₂ eq (100 years) |

¹ The voltage refers to the operating voltage of the main components and can deviate from the supply voltage by using a transformer.