

manufacturer: ait-deutschland GmbH			
Model	cBoxX 60		
Option high-temperature	Yes		
Voltage ¹	400/3/50		
Type of condensing	air-cooled		
Refrigerant fluid	R410A		
Item	Symbol	Value	Unit
Operating temperature	t	7	°C
Seasonal energy performance ratio	SEPR	4,56	
Annual electricity consumption	Q	71.046	kWh/a
Parameters at full load and reference ambient temperature at rating point A			
Rated refrigeration capacity	P _A	43,72	kW
Rated power input	D _A	18,93	kW
Rated energy efficiency ratio	EER _{DC,A}	2,31	
Parameters at rating point B			
Declared refrigeration capacity	P _B	49,88	kW
Declared power input	D _B	16,34	kW
Declared energy efficiency ratio	EER _{DC,B}	3,05	
Parameters at rating point C			
Declared refrigeration capacity	P _C	53,79	kW
Declared power input	D _C	12,93	kW
Declared energy efficiency ratio	EER _{DC,C}	4,16	
Parameters at rating point D			
Declared refrigeration capacity	P _D	54,38	kW
Declared power input	D _D	11,68	kW
Declared energy efficiency ratio	EER _{DC,D}	4,66	
Other Items			
Capacity control	staged		
Degradation co-efficient chillers (rating point B)	C _{dc}	0,99	
Degradation co-efficient chillers (rating point C)	C _{dc}	0,99	
Degradation co-efficient chillers (rating point D)	C _{dc}	0,99	
GWP of the refrigerant		2088	kg CO ₂ eq (100 years)

¹ The voltage refers to the operating voltage of the main components and can deviate from the supply voltage by using a transformer.