

manufacturer: ait-deutschland GmbH			
Model	cBoxX 60		
Option high-temperature	No		
Voltage ¹	400/3/50		
Type of condensing	air-cooled		
Refrigerant fluid	R410A		
Item	Symbol	Value	Unit
Operating temperature	t	7	°C
Seasonal energy performance ratio	SEPR	4,75	
Annual electricity consumption	Q	64.100	kWh/a
Parameters at full load and reference ambient temperature at rating point A			
Rated refrigeration capacity	P _A	41,11	kW
Rated power input	D _A	18,03	kW
Rated energy efficiency ratio	EER _{DC,A}	2,28	
Parameters at rating point B			
Declared refrigeration capacity	P _B	47,04	kW
Declared power input	D _B	15,23	kW
Declared energy efficiency ratio	EER _{DC,B}	3,09	
Parameters at rating point C			
Declared refrigeration capacity	P _C	52,69	kW
Declared power input	D _C	12,64	kW
Declared energy efficiency ratio	EER _{DC,C}	4,17	
Parameters at rating point D			
Declared refrigeration capacity	P _D	54,33	kW
Declared power input	D _D	11,67	kW
Declared energy efficiency ratio	EER _{DC,D}	4,66	
Other Items			
Capacity control	staged		
Degradation co-efficient chillers (rating point B)	C _{dc}	0,99	
Degradation co-efficient chillers (rating point C)	C _{dc}	0,99	
Degradation co-efficient chillers (rating point D)	C _{dc}	0,99	
GWP of the refrigerant		2088	kg CO ₂ eq (100 years)

¹ The voltage refers to the operating voltage of the main components and can deviate from the supply voltage by using a transformer.