

manufacturer: ait-deutschland GmbH			
Model	cBoxX 70		
Option high-temperature	No		
Voltage ¹	460/3/60		
Type of condensing	air-cooled		
Refrigerant fluid	R410A		
Item	Symbol	Value	Unit
Operating temperature	t	7	°C
Seasonal energy performance ratio	SEPR	5,32	
Annual electricity consumption	Q	76.910	kWh/a
Parameters at full load and reference ambient temperature at rating point A			
Rated refrigeration capacity	P _A	55,18	kW
Rated power input	D _A	19,84	kW
Rated energy efficiency ratio	EER _{DC,A}	2,78	
Parameters at rating point B			
Declared refrigeration capacity	P _B	62,46	kW
Declared power input	D _B	16,78	kW
Declared energy efficiency ratio	EER _{DC,B}	3,72	
Parameters at rating point C			
Declared refrigeration capacity	P _C	71,62	kW
Declared power input	D _C	13,83	kW
Declared energy efficiency ratio	EER _{DC,C}	5,18	
Parameters at rating point D			
Declared refrigeration capacity	P _D	74,50	kW
Declared power input	D _D	11,23	kW
Declared energy efficiency ratio	EER _{DC,D}	6,63	
Other Items			
Capacity control	staged		
Degradation co-efficient chillers (rating point B)	C _{dc}	0,98	
Degradation co-efficient chillers (rating point C)	C _{dc}	0,97	
Degradation co-efficient chillers (rating point D)	C _{dc}	0,97	
GWP of the refrigerant		2088	kg CO ₂ eq (100 years)

¹ The voltage refers to the operating voltage of the main components and can deviate from the supply voltage by using a transformer.