

manufacturer: ait-deutschland GmbH			
Model	cBoxX 70		
Option high-temperature	No		
Voltage ¹	400/3/50		
Type of condensing	air-cooled		
Refrigerant fluid	R410A		
Item	Symbol	Value	Unit
Operating temperature	t	7	°C
Seasonal energy performance ratio	SEPR	5,49	
Annual electricity consumption	Q	69.738	kWh/a
Parameters at full load and reference ambient temperature at rating point A			
Rated refrigeration capacity	P _A	51,68	kW
Rated power input	D _A	18,77	kW
Rated energy efficiency ratio	EER _{DC,A}	2,75	
Parameters at rating point B			
Declared refrigeration capacity	P _B	58,64	kW
Declared power input	D _B	15,62	kW
Declared energy efficiency ratio	EER _{DC,B}	3,75	
Parameters at rating point C			
Declared refrigeration capacity	P _C	65,04	kW
Declared power input	D _C	12,70	kW
Declared energy efficiency ratio	EER _{DC,C}	5,12	
Parameters at rating point D			
Declared refrigeration capacity	P _D	70,94	kW
Declared power input	D _D	9,75	kW
Declared energy efficiency ratio	EER _{DC,D}	7,27	
Other Items			
Capacity control	staged		
Degradation co-efficient chillers (rating point B)	C _{dc}	0,97	
Degradation co-efficient chillers (rating point C)	C _{dc}	0,97	
Degradation co-efficient chillers (rating point D)	C _{dc}	0,96	
GWP of the refrigerant		2088	kg CO ₂ eq (100 years)

¹ The voltage refers to the operating voltage of the main components and can deviate from the supply voltage by using a transformer.