

manufacturer: ait-deutschland GmbH			
Model	cBoxX 80		
Option high-temperature	Yes		
Voltage ¹	400/3/50		
Type of condensing	air-cooled		
Refrigerant fluid	R410A		
Item	Symbol	Value	Unit
Operating temperature	t	7	°C
Seasonal energy performance ratio	SEPR	4,68	
Annual electricity consumption	Q	95.529	kWh/a
Parameters at full load and reference ambient temperature at rating point A			
Rated refrigeration capacity	P _A	60,38	kW
Rated power input	D _A	24,08	kW
Rated energy efficiency ratio	EER _{DC,A}	2,51	
Parameters at rating point B			
Declared refrigeration capacity	P _B	68,86	kW
Declared power input	D _B	20,48	kW
Declared energy efficiency ratio	EER _{DC,B}	3,36	
Parameters at rating point C			
Declared refrigeration capacity	P _C	78,64	kW
Declared power input	D _C	17,15	kW
Declared energy efficiency ratio	EER _{DC,C}	4,59	
Parameters at rating point D			
Declared refrigeration capacity	P _D	83,92	kW
Declared power input	D _D	14,34	kW
Declared energy efficiency ratio	EER _{DC,D}	5,85	
Other Items			
Capacity control	staged		
Degradation co-efficient chillers (rating point B)	C _{dc}	0,98	
Degradation co-efficient chillers (rating point C)	C _{dc}	0,98	
Degradation co-efficient chillers (rating point D)	C _{dc}	0,97	
GWP of the refrigerant		2088	kg CO ₂ eq (100 years)

¹ The voltage refers to the operating voltage of the main components and can deviate from the supply voltage by using a transformer.