

manufacturer: ait-deutschland GmbH			
Model	cBoxX 80		
Option high-temperature	No		
Voltage ¹	400/3/50		
Type of condensing	water-cooled		
Refrigerant fluid	R410A		
Item	Symbol	Value	Unit
Operating temperature	t	7	°C
Seasonal energy performance ratio	SEPR	7,62	
Annual electricity consumption	Q	63.712	kWh/a
Parameters at full load and reference ambient temperature at rating point A			
Rated refrigeration capacity	P _A	65,56	kW
Rated power input	D _A	16,96	kW
Rated energy efficiency ratio	EER _{DC,A}	3,86	
Parameters at rating point B			
Declared refrigeration capacity	P _B	72,84	kW
Declared power input	D _B	13,82	kW
Declared energy efficiency ratio	EER _{DC,B}	5,27	
Parameters at rating point C			
Declared refrigeration capacity	P _C	78,12	kW
Declared power input	D _C	11,24	kW
Declared energy efficiency ratio	EER _{DC,C}	6,95	
Parameters at rating point D			
Declared refrigeration capacity	P _D	83,84	kW
Declared power input	D _D	7,98	kW
Declared energy efficiency ratio	EER _{DC,D}	10,51	
Other Items			
Capacity control	staged		
Degradation co-efficient chillers (rating point B)	C _{dc}	0,96	
Degradation co-efficient chillers (rating point C)	C _{dc}	0,95	
Degradation co-efficient chillers (rating point D)	C _{dc}	0,93	
GWP of the refrigerant		2088	kg CO ₂ eq (100 years)

¹ The voltage refers to the operating voltage of the main components and can deviate from the supply voltage by using a transformer.