

manufacturer: ait-deutschland GmbH			
Model	cBoxX 90		
Option high-temperature	No		
Voltage ¹	400/3/50		
Type of condensing	water-cooled		
Refrigerant fluid	R410A		
Item	Symbol	Value	Unit
Operating temperature	t	7	°C
Seasonal energy performance ratio	SEPR	7,51	
Annual electricity consumption	Q	74.444	kWh/a
Parameters at full load and reference ambient temperature at rating point A			
Rated refrigeration capacity	P _A	75,42	kW
Rated power input	D _A	19,22	kW
Rated energy efficiency ratio	EER _{DC,A}	3,92	
Parameters at rating point B			
Declared refrigeration capacity	P _B	83,62	kW
Declared power input	D _B	15,58	kW
Declared energy efficiency ratio	EER _{DC,B}	5,37	
Parameters at rating point C			
Declared refrigeration capacity	P _C	89,38	kW
Declared power input	D _C	12,80	kW
Declared energy efficiency ratio	EER _{DC,C}	6,98	
Parameters at rating point D			
Declared refrigeration capacity	P _D	94,32	kW
Declared power input	D _D	9,48	kW
Declared energy efficiency ratio	EER _{DC,D}	9,95	
Other Items			
Capacity control	staged		
Degradation co-efficient chillers (rating point B)	C _{dc}	0,96	
Degradation co-efficient chillers (rating point C)	C _{dc}	0,95	
Degradation co-efficient chillers (rating point D)	C _{dc}	0,93	
GWP of the refrigerant		2088	kg CO ₂ eq (100 years)

¹ The voltage refers to the operating voltage of the main components and can deviate from the supply voltage by using a transformer.